



Tery MRRINE - Professional Pumps for Marine Use







With a Company Ethos of continuous Improvement and the innovation of manufacturing materials. Teryair have developed New Product Ranges allowing us to enter new markets and offer pumping solutions for more applications.

To simplify the Introduction of these new products? Teryair have broken down their Portfolio into segments.

What was the original Teryair range Has now been branded as TeryMarine. This range is still the most popular. and has a multitude of applications.


Not just for Marine, this range is also the 'workhorse' of the AODD range. All The TeryMarine range are ATEX compliant, for hazardous environments.

2" Aluminium



2" Aluminium IMPA 591603


Performance Graphs - Nitrile/Santoprene



Technical Data

Pump Size		1/2″	1″	1-1/2"	2"	3″
Air Inlet, NPT		1/2" Nipple	1/4"	1/2"	3/4"	3/4"
Max. Size Solids		1.6	3.2	4.8	6.4	9.5
mm (Inch)		(1/16")	(1/8")	(3/16")	(1/4")	(3/8")
Max. Flow Rate		27	122	285	591	878
lpm (gpm)		(6.5)	(32)	(75)	(155)	(232)
Weight,	Aluminum	4.4	9.1	15	26.5	52.5
Kgs (Lbs)		(9.7)	(20)	(33)	(58)	(115.5)
Max. Suction Lift		5.5	5.5	5.5	6.4	5.5
Dry M(Ft)		(18)	(18)	(18)	(21)	(18)
Max. Suction Lift		9.5	9.5	8.5	8.5	9.5
Wet M(Ft)		(31)	(31)	(28)	(28)	(31)

Dimensions in mm - Aluminium



Pump Nomenclature

